


2 **STELLAR Digital Lightning Strike Counter**



GENERAL DESCRIPTIONS

STELLAR Digital Lightning Strike Counter provide high sensitive results with a digital displaying screen. Durable to sun light, dust and water.



- > Fully compatible with standards
- > Displaying screen 6 digits
- > High Quality Plastic and Stainless Steel Material
- > 20 years Warranty under ORBITAL experience
- > Testable with ORBITAL Testing Units Easy Application



TECHNICAL CHARACTERISTICS

| | |
|-----------------------|--|
| Current Sensitivity | 1500 A 8/20 ms impulse |
| Operating Range | 1500 A, Max. 200kA 8/20 ms |
| Displaying | Digital 6 Digits |
| Dimensions (mm) | 70(D) x 100(H) x 50(W) |
| Weight | 0.59 kg |
| Mounting/Connecting | Double Ø6-10 UV Plastic Cable or 50x5 mm tape |
| Construction | Polycarbonate enclosure |
| Water Resistance | IP67 |
| Operating Temperature | -15C to 65C |
| Colour Option | ● Black ○ White |
| Inner Fixing | Polyurethane resin |

CONDUCTING OPTIONS

| | |
|---|------------------------------------|
|  | Flat Tape: 50 x 5 mm |
|  | Cable & Wire: 6-10 mm Ø |